

# Product data sheet

Specifications



## APC Back-UPS 600VA, 120V, 1 USB charging port, 7 NEMA outlets (2 surge)

BE600M1

### Overview

Lead Time Usually in Stock

### Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Rated Power In W	330 W
Rated Power In Va	600 VA
Product Or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA 5-15P
Output Connection Type	5 NEMA 5-15R 2 NEMA 5-15R surge
Cable Length	5 ft (1.52 m)
Battery Type	Lead-acid battery
Provided Equipment	User manual

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	10 h
Number Of Battery Replacement Quantity	1
Battery Charger Power	7 W rated
Battery Power In Vah	78 VAh capacity 66 VAh runtime
Battery Life	3...5 year(s)
Replacement Battery	<a href="#">APCRBC154</a>
Extended Runtime	0

### General

Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0

Redundant	No
-----------	----

## Physical

Height	5.47 in (13.9 cm)
Width	10.79 in (27.4 cm)
Depth	4.13 in (10.5 cm)
Net Weight	7.69 lb(US) (3.49 kg)
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

## Input

Network Frequency	50/60 Hz +/- 3 Hz auto-sensing
Input Voltage Limits	92...139 V

## Output

Maximum Configurable Power In W	330 W
Output Frequency	50/60 Hz +/- 3 Hz sync to mains
Ups Type	Standby
Wave Type	Stepped approximation to a sinewave
Maximum Configurable Power In Va	600 VA
Transfer Time	6 ms typical : 10 ms maximum

## Conformance

Product Certifications	California Energy Commission (CEC) cTUVus NOM
Equipment Protection Policy	Lifetime : \$75000

## Environmental

Ambient Air Temperature For Operation	32...104 °F (0...40 °C)
Relative Humidity	0...90 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage Altitude	0...50000 ft (0.00...15240.00 m)
Acoustic Level	35 dBA
Heat Dissipation	16 Btu/h

## Communications & Management

Control Panel	LED status display with on line : on battery : replace battery and overload indicators
---------------	--

---

<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
--------------	--

---

## Surge Protection and Filtering

---

<b>Surge Energy Rate</b>	490 J
<b>Noise Suppression</b>	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449
<b>Let Through Voltage Rating</b>	5 V

---

## Packing Units

---

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	7.72 in (19.6 cm)
<b>Package 1 Width</b>	6.61 in (16.8 cm)
<b>Package 1 Length</b>	14.29 in (36.3 cm)
<b>Package 1 Weight</b>	8.40 lb(US) (3.81 kg)
<b>Scc14</b>	10731304325113

---

## Contractual warranty

---

<b>Warranty</b>	3 years repair or replace
-----------------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)



Energy Efficient Take-back Transparency RoHS/REACH

### Resource performance

Energy Efficient Product

---

Take-Back Program Available

---

### Well-being performance

Mercury Free

---

Rohs Exemption Information [Yes](#)

---

### Certifications & Standards

Reach Regulation [REACH Declaration](#)

---

Eu Rohs Directive [Compliant with Exemptions](#)

---

Environmental Disclosure [Product Environmental Profile](#)

---

Circularity Profile [End of Life Information](#)

---