

Product data sheet

Specifications



Ecostruxure Micro Data Center, with 42U SX rack, 5kVA, 208V, 60 Hz, pre assembled, 1991H x 600W x 1070D mm

MDC42SX5KVAT

Overview

Presentation A pre-assembled Micro Data Center includes: shock packaged rack, two UPS, two switched rack PDUs, NetBotz 250 with rack access handles, one temperature/ humidity probe, blanking panels, and brush strip.

Lead Time Usually in Stock

Main

Product Or Component Type Micro data center

Physical

Height 78.39 in (199.1 cm)

Width 23.62 in (60 cm)

Depth 42.13 in (107 cm)

Number Of Rack Unit 42U

Net Weight 620.01 lb(US) (281.23 kg)

Mounting Mode Not rack-mountable

Minimum Mounting Depth 7.52 in (19.1 cm)

Mounting Preference No preference

Maximum Mounting Depth 36.02 in (91.49 cm)

Max Cto Ship Weight 2000 lb(US) (907.18 kg)

Baying Included No

Permanent Permissible Load 2250 lb(US) (1020.58 kg) dynamic
3000 lb(US) (1360.78 kg) static

Marking 14 gauge EIA mounting rail
16 gauge front door
16 gauge post
18 gauge rear door
18 gauge roof
18 gauge side panels

Packing Units

Unit Type Of Package 1 PCE

Number Of Units In Package 1 1

Package 1 Height 85.79 in (217.9 cm)

Package 1 Width 52.01 in (132.1 cm)

Package 1 Length 43.50 in (110.5 cm)

Package 1 Weight 874.99 lb(US) (396.89 kg)

Contractual warranty

Warranty

1 Year

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information
