

# Product data sheet

Specifications



## APC Essential SurgeArrest PE63, 6 Outlets, 3 Foot Cord, 120V

PE63

⚠ Discontinued on: Feb 7, 2024

⚠ To be end-of-service on: Feb 7, 2025

⚠ Discontinued - Service only

### Overview

Lead Time Usually in Stock

### Main

Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Cable Length	3 ft (0.91 m)
Number Of Cables	1
Provided Equipment	User manual

### Physical

Colour	Black Grey
Height	1.18 in (3 cm)
Width	2.05 in (5.2 cm)
Depth	11.02 in (28 cm)
Net Weight	0.79 lb(US) (0.36 kg)
Mounting Preference	No preference
Mounting Mode	Not rack-mountable

### Input

Input Power	1200 W
Maximum Line Current	15 A
Network Frequency	50/60 Hz
Maximum Input Current	15 A
Switching Current Capacity	15 A

### Output

Number Of Power Socket Outlets	6
Outlet Standard	NEMA 5-15R

### Conformance

UI 1449 Tvss Rating	500
---------------------	-----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

<b>Product Certifications</b>	MET Canada MET USA
<b>Standards</b>	UL 1363 UL 1449
<b>Equipment Protection Policy</b>	Lifetime : \$50000

## Environmental

<b>Ambient Air Temperature For Operation</b>	32...104 °F (0...40 °C)
<b>Relative Humidity</b>	0...95 % non-condensing
<b>Operating Altitude</b>	0...10000 ft
<b>Ambient Air Temperature For Storage</b>	5...113 °F (-15...45 °C)
<b>Storage Relative Humidity</b>	0...95 % non-condensing
<b>Storage Altitude</b>	0...50000 ft (0.00...15240.00 m)

## Surge Protection and Filtering

<b>Response Time</b>	1 ns common mode
<b>Common Mode Rejection</b>	40 dB
<b>Peak Current</b>	24 kAcommon mode 12 kAnormal mode
<b>Surge Energy Rate</b>	540 J

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	1.26 in (3.2 cm)
<b>Package 1 Width</b>	12.60 in (32 cm)
<b>Package 1 Length</b>	3.86 in (9.8 cm)
<b>Package 1 Weight</b>	0.42 lb(US) (0.19 kg)
<b>Scc14</b>	10731304328824

## Contractual warranty

<b>Warranty</b>	Limited Lifetime
-----------------	------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)



Transparency RoHS/REACH

## Well-being performance

Reach Free Of Svhc

---

Lead Free

---

Mercury Free

---

Rohs Exemption Information [Yes](#)

---

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

---

Eu Rohs Directive [Compliant with Exemptions](#)

---

Environmental Disclosure [Product Environmental Profile](#)

---

Circularity Profile [End of Life Information](#)

---