

Product data sheet

Specifications



APC Symmetra LX 8kVA Scalable to 16kVA N+1 Rack-mount, 208/240V

SYA8K16RMP

Overview

Lead Time Usually in Stock

Main

Main Input Voltage	208 V
Other Input Voltage	240 V
Main Output Voltage	120 V 208 V
Other Output Voltage	240 V
Rated Power In W	6400 W
Rated Power In Va	8000 VA
Output Connection Type	8 NEMA L5-20R 4 NEMA L14-30R
Output Connector Type	Hard wire 4-wire (2P + N + E) 1
Number Of Rack Unit	19U
Battery Type	Lead-acid battery
Provided Equipment	CD with software Documentation CD Installation guide Rack mounting support rails User manual Web/SNMP management card

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number Of Battery Filled Slots	2
Number Of Battery Free Slots	2
Battery Recharge Time	3 h
Additional Information	Configurable for 120/208 or 120/240 output voltage
Battery Charger Power	574 W rated
Battery Life	3...5 year(s)
Extended Runtime	1

General

Product Web Sub-Family 4kVA power increments

Number Of Power Module Free Slots	3
Number Of Power Module Filled Slots	2
Redundant	Yes

Physical

Colour	Black Silver
Height	32.91 in (83.6 cm)
Width	18.58 in (47.2 cm)
Depth	27.09 in (68.8 cm)
Net Weight	437.93 lb(US) (198.64 kg)
Mounting Location	Front
Mounting Preference	Lower
Mounting Mode	Rack-mounted
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	45...65 Hz auto-sensing
Number Of Input Connectors	1 hard wire 4-wire (2P + N + E)
Input Voltage Limits	96...138 V line to neutral
Input Harmonic Distortion	Less than 7 % for full load
Input Power Factor At Full Load	0.98

Output

Maximum Configurable Power In W	12800 W
Harmonic Distortion	Less than 5 % at full load
Output Frequency	47...63 Hz sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
Crest Factor	Up to 5 : 1
Ups Type	Double conversion online
Wave Type	Sine wave
Bypass Type	Internal bypass (automatic and manual) Optional external bypass
Maximum Output Current	37 A
Maximum Configurable Power In Va	16000 VA

Conformance

Product Certifications	CSA
Standards	FCC part 15 class A OSHDP UL 1778

Environmental

Ambient Air Temperature For Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage Altitude	0...15000 ft (0.00...4572.00 m)
Acoustic Level	62 dBA
Heat Dissipation	4995 Btu/h

Communications & Management

Free Slots	1
Preinstalled Device	Network management card 2 with environmental monitoring
Control Panel	Multifunction LCD status and control console
Alarm	Audible and visible alarms : prioritized by severity
Emergency Power Off	Yes

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	41.50 in (105.4 cm)
Package 1 Width	39.25 in (99.7 cm)
Package 1 Length	23.58 in (59.9 cm)
Package 1 Weight	528.14 lb(US) (239.56 kg)

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Energy Efficient Take-back RoHS/REACH

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information
