

Product data sheet

Specifications



InRow RC, 600mm, Chilled Water 460-480V 60Hz, w/ humidifier

ACRC601P

Overview

Lead Time Special Order - Call for Quoted Lead Times

Main

Main Input Voltage	460 V 3 phases 480 V 3 phases
Number Of Rack Unit	42U
Number Of Cables	2
Provided Equipment	Installation guide Operations and maintenance manual

General

Humidification Flow	6.6 lb/hr (2.99 kg/hr)
Air Discharge Option	Horizontal
Intake Air Option	Rear return
Air Flow	6000 ft ³ /min (2831.68 l/s)
Minimum Water Inlet Temperature	45 °F (7 °C)
Condensate Pump Flow	8.45 Gal/hr(US) (0.03 m3/h)

Physical

Colour	Black
Height	78.39 in (199.1 cm)
Width	23.62 in (60 cm)
Depth	42.13 in (107 cm)
Net Weight	777.64 lb(US) (352.73 kg)
Mounting Preference	No preference
Mounting Mode	Not rack-mountable

Input

Input Power	14000 W
Network Frequency	60 Hz +/- 3 Hz
Number Of Input Connectors	1 hard wire 4-wire (3P + E)

Conformance

Product Certifications	cUL listed Industry Canada UL listed
Standards	FCC part 15 class A

Communications & Management

Control Panel	Multifunction LCD status and control console
----------------------	--

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	85.28 in (216.6 cm)
Package 1 Width	44.76 in (113.7 cm)
Package 1 Length	33.46 in (85 cm)
Package 1 Weight	1021.14 lb(US) (463.18 kg)
Number Of Units In Package 3	1

Contractual warranty

Warranty	1 year (parts only), 1 year on-site repair or replace with factory authorized Start-Up
-----------------	--

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)

Eu Rohs Directive

Not applicable, out of EU RoHS legal scope
