

# Product data sheet

Specifications



## APC NetShelter 6U Wallmount Rack Enclosure Cabinet Single Hinged Server Depth

AR106SH6

### Overview

<b>Presentation</b>	Ideal for retail, healthcare, and educational facilities, this wall mount rack offers an efficient solution for deploying server and networking equipment for edge computing applications. This rack enclosure is wall mountable, ideal for areas with limited floor space, and is designed specifically for servers and network switches, and patch panels. The cabinet's door is reversible and is compatible with APC's Netbotx security upgrade to provide remote access, video surveillance, and environmental monitoring (sold separately). Optional 120V fan tray can be top or bottom mounted (sold separately) Both the top and bottom feature knockouts of 1/2U mounting space for accessories. And several APC Smart-UPS models low-profile provide easy UPS integration and mounting 6U Wall mount cabinet, the mounting depth range of 2.87 to 20.8 inches, 200lb weight capacity, 19" rack width, ships fully assembled, ventilated with accessory integration options, 5 year APC warranty.
---------------------	--

<b>Lead time</b>	Usually in Stock
------------------	------------------

### Main

<b>Product or component type</b>	Rack enclosure
----------------------------------	----------------

<b>Number of rack unit</b>	6U
----------------------------	----

### Physical

<b>Height</b>	13.98 in (35.5 cm)
---------------	--------------------

<b>Width</b>	23.62 in (60 cm)
--------------	------------------

<b>Depth</b>	23.62 in (60 cm)
--------------	------------------

<b>Net weight</b>	31.70 lb(US) (14.38 kg)
-------------------	-------------------------

<b>Colour</b>	Black
---------------	-------

<b>Mounting support</b>	Wall
-------------------------	------

<b>Mounting preference</b>	No preference
----------------------------	---------------

<b>Mounting mode</b>	Not rack-mountable
----------------------	--------------------

<b>Maximum mounting depth</b>	20.80 in (52.83 cm)
-------------------------------	---------------------

<b>minimum mounting depth</b>	2.87 in (7.29 cm)
-------------------------------	-------------------

<b>Rack width</b>	19"
-------------------	-----

<b>Permanent permissible load</b>	200 lb(US) (90.7 kg) static
-----------------------------------	-----------------------------

### Conformance

<b>Product certifications</b>	TAA compliance UL
-------------------------------	----------------------

<b>Standards</b>	UL 2416 EIA-310E
------------------	---------------------

### Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	17.13 in (43.5 cm)
<b>Package 1 Width</b>	26.97 in (68.5 cm)
<b>Package 1 Length</b>	26.97 in (68.5 cm)
<b>Package 1 Weight</b>	38.60 lb(US) (17.51 kg)

## Contractual warranty

<b>Warranty</b>	5 year repair or replace
-----------------	--------------------------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	53
--	----

## Use Better

### Materials and Substances

[EU RoHS Directive](#)

Pro-active compliance (Product out of EU RoHS legal scope)

REACH Regulation

[REACH Declaration](#)

China RoHS Regulation

[China RoHS declaration](#)

### Energy efficiency

Optimized Energy Efficiency

Energy efficient product

## Use Again

### Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Take-back

Yes