Product data sheet

Specifications



APC Replacement Battery Cartridge for Back-UPS, 12V 9Ah lead-acid battery, 2-year repair or replace warranty

RBC17

Main

Product or component type	Replacement battery cartridge
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	All required connectors Battery recycling guide Reusable packaging Installation guide

Batteries & Runtime

Battery location	Internal battery
Number of battery free slots	0
Number of battery filled slots	0
Device mounting	Stand alone battery stack
Battery voltage	12 V
Number of battery replacement quantity	1

Physical

Colour	Black
Height	2.6 in (65 mm)
Width	3.7 in (94 mm)
Depth	5.9 in (151 mm)
Net weight	5.71 lb(US) (2.59 kg)
Mounting mode	Not rack-mountable
USB compatible	No

Output

Battery capacity	9.0 Ah

Environmental

Ambient air temperature for operation	32…104 °F (0…40 °C)
Operating altitude	0...10000 ft
Relative humidity	0…95 %
Ambient air temperature for storage	5…113 °F (-15…45 °C)
Storage altitude	0…50000 ft (0…15240 m)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Storage Relative Humidity	0…95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.504 in (8.900 cm)
Package 1 Width	6.890 in (17.500 cm)
Package 1 Length	8.386 in (21.300 cm)
Package 1 Weight	6.305 lb(US) (2.860 kg)
Unit Type of Package 2	P12
Number of Units in Package 2	48
Package 2 Height	31.496 in (80.000 cm)
Package 2 Width	31.496 in (80.000 cm)
Package 2 Length	47.244 in (120.000 cm)
Package 2 Weight	306.037 lb(US) (138.816 kg)

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**19 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**10 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.4 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.2 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**1 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**7 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Average percentage of recycled plastic content	**15 %**
Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**

Use Again

Repack and remanufacture

Recyclability potential, in %	**1**
Circularity Profile	**End of Life Information**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**

Image of product / Alternate images

Alternative

